


**DECLARATION OF PERFORMANCE**  
No. 001DP2013

1. Unique identification code of the product type  
Type, batch or serial number or any other element allowing identification of the product  
**Dry-pressed ceramic tiles, with water absorption E > 10%**
2. Intended use (s)  
**For internal walls**
3. Name or registered trade mark, and contact address of the manufacturer  
**NOVOGRES, S.A. Ctra. N-340 km 56,7 Vila-real, Castellón, España**
4. System (s) of assessment and verification of constancy of performance (AVCP)  
**System 4**
5. Name and identification number of notified laboratory, if relevant  
Task(s) carried out, AVCP system, Document issued and date of issue  
**DOES NOT APPLY**
6. Prestaciones declaradas

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1	EN 14411:2012
Release of dangerous substance, for:		
- Cadmium	PND	
- Lead	PND	
Bond strength/adhesión, for:		
Cementitious adhesive, type C1	> 0,5 N/mm <sup>2</sup>	
Durability for:		
- Internal use:	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.  
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.  
Signed for and on behalf of the manufacturer by:

  
 Juan S. Bano Pesudo  
 General manager


**DECLARATION OF PERFORMANCE**  
No. 002DP2013

1. Unique identification code of the product type  
Type, batch or serial number or any other element allowing identification of the product  
**Dry-pressed ceramic tiles, with water absorption  $3\% < E \leq 6\%$**
2. Intended use(s)  
**For internal walls and floorings**
3. Name or registered trade mark, and contact address of the manufacturer  
**NOVOGRES, S.A. Ctra. N-340 km 56,7 Vila-real, Castellón, España**
4. System(s) of assessment and verification of constancy of performance (AVCP)  
**System 4**
5. Name and identification number of notified laboratory, if relevant  
Task(s) carried out, AVCP system, Document issued and date of issue  
**DOES NOT APPLY**

6. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1FL / A1	EN 14411:2012
Release of dangerous substance, for:		
- Cadmium	PND	
- Lead	PND	
Breaking strength	> 1000 N	
Slipperiness, as:	PND	
Adhesion:		
Cementitious adhesive, type C1	> 0,5 N/mm <sup>2</sup>	
Durability for:		
- internal use:	Pass	
Tactility	PND	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.  
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.  
Signed for and on behalf of the manufacturer by:


  
 Juan S. Bono Pasudo  
 General manager

**DECLARATION OF PERFORMANCE**  
No. 003DP2013

1. Unique identification code of the product type  
Type, batch or serial number or any other element allowing identification of the product  
**Dry-pressed ceramic tiles, with water absorption  $0,5\% < E \leq 3\%$**
2. Intended use(s)  
**For internal walls and floorings**
3. Name or registered trade mark, and contact address of the manufacturer  
**NOVOGRES, S.A. Ctra. N-340 km 56,7 Vila-real, Castellón, España**
4. System(s) of assessment and verification of constancy of performance (AVCP)  
**System 4**
5. Name and identification number of notified laboratory, if relevant  
Task(s) carried out, AVCP system, document issued and date of issue  
**DOES NOT APPLY**
6. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1FL / A1	EN 14411:2012
Release of dangerous substance, for:		
- Cadmium	PND	
- Lead	PND	
Breaking strength	> 1100 N	
Slipperiness, as:	PND	
Adhesion:		
Cementitious adhesive, type C1	> 0,5 N/mm <sup>2</sup>	
Durability for:		
- Internal use:	Pass	
Tactility	PND	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.  
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.  
Signed for and on behalf of the manufacturer by:

  
 Juan S. Bono Resudo  
 General manager

**DECLARATION OF PERFORMANCE**  
No. 004DP2013

1. Unique identification code of the product type  
Type, batch or serial number or any other element allowing identification of the product  
**Dry-pressed ceramic tiles, with water absorption  $E \leq 0,5\%$**

2. Intended use(s)  
**For internal and external walls and floorings**

3. Name or registered trade mark, and contact address of the manufacturer  
**NOVOGRES, S.A. Ctra. N-340 km 56,7 Vila-real, Castellón, España**


4. System(s) of assessment and verification of constancy of performance (AVCP)  
**System 4**

5. Name and identification number of notified laboratory, if relevant  
Task(s) carried out, AVCP system, document issued and date of issue  
**DOES NOT APPLY**

6. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1FL / A1	EN 14411:2012
Release of dangerous substance, for:		
- Cadmium	PND	
- Lead	PND	
Breaking strength	> 1300 N	
Slipperiness, as:	PND	
Adhesion:		
Cementitious adhesive, type C2	> 1 N/mm <sup>2</sup>	
Durability for:		
- Internal use:	Pass	
- External use: freeze-thaw resistance	Pass	
Tactility	PND	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.  
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.  
Signed for and on behalf of the manufacturer by:

  
 Juan S. Bono Pesudo  
 General manager